No. DoP-0493-CPR-W045

1. Unique identification code of the product-type or product family: Vinyl wallcovering 001

2. Type, batch or serial number or any other element allowing identification of the construction product:

Vinyl wallcovering consisting of a top vinyl layer, protected with a special coating and a non-woven backing

3. Intended uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Use as wall covering(s) within a building according to the manufacturer's specifications and installation practices in accordance with EN 15102:2007+A1:2011

Lay on interior or partition walls with a fire-retardant specification of A2-S1-d0 or better, use Vinylpex adhesive.

Product type: vinyl wallcovering consisting of a top vinyl layer, protected with a special coating and non-woven backing.

Waterproof, UV resistant

4. Name, registered trade name or registered trade mark and contact address of the manufacturer:

Przedsiębiorstwo Powlekania Tkanin Vinylpex Robinscy spółka jawna, ul. Hiacyntowa 39, 60-175 Poznań, Poland

5. System of assessment and verification of constancy of performance of the construction product: SYSTEM 1

6. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Centexbel NB0493 performed the determination of the product type on the basis of type testing (including sampling), initial inspection of the manufacturing plant and of factory production control, continuous surveillance, assessment and evaluation of factory production control under system 1 and issued the certificate of constancy of performance: 0493-CPR-W045

7. Declared performance:

Essential characteristic	Performance	Harmonised technical specification	Essential characteristic	Performance	Harmonised technical specification
Reaction to fire EN 13501-1	B-s1, d0	EN 15102:2007 A1:2011	Release of vinyl chloride monomer EN 12149-B	< 0.2 mg / kg	EN 15102:2007 A1:2011
Release of formaldehyde EN 12149-C	< 120 mg / kg		Sound absorption ISO 354	NPD	
Release of heavy metals EN 12149-A	Antimony < 0.1 mg/kg Arsenic < 0.1 mg/kg Barium < 0.1 mg/kg Cadmium < 0.3 mg/kg Chromium < 0.1 mg/kg Lead < 0.5 mg/kg Mercury < 0.1 mg/kg Selenium < 1 mg/kg		Thermal resistance «EN 12524» or «EN 12667»	NPD	

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: Paweł Rosada – Sales Director

(name and function):

(place and date of issue) : Poznań, 28.01.2025

Przedsiębiorstwo Powiekania Tkanin VINYLPEX Robińscy

Spółka Jawna 60-175 Poznań 27, ul. Hiacyntowa 39 tel. Zarzad 867-70-48, 867-70-40, 867-70-66

tel. Zerząd 867-70-48, 887-70-40, 867-70-69 Zbył 867-76-00, fax 867-76-01 NIP 779-00-01-404, Regon 004832571

(signature)